



Trans Video Deutschland
Vertriebs GmbH

Electronic Large Screen Displays
for Information and Advertising
Display and Monitor Systems
Large Screen Video/Data
Projection Systems
Video Walls
Verkauf/Vermietung/Service

EP739

Bright and Versatile Business Projector

The Optoma EP739 is a versatile highly specified multi-media projector equally at home in the boardroom, classroom, on the road or showing movies. Brighter and lighter, these projectors pack more performance into smaller boxes than ever before. The exceptional brightness, astonishing 2000:1 contrast ratio and XGA resolution ensures that your presentations have serious impact

- **5000 Hour lamp life** for low cost of ownership
- Brightness of **2300 lumens**, for powerful presentations
- Superior **Contrast at 2000:1** for unparalleled image clarity
- Convenient **DVI-HDCP, RGB SCART**, Component, S-Video and composite video connectivity
- Exceptionally **Quiet 32dB** for unobtrusive operation
- Ultra portable **lightweight, only 2.4kg**
- **sRGB** for accurate colour matching
- **Short-Throw Lens** option for a bigger picture in a smaller space



Specifications

Resolution	Native: XGA 1024 x 768 up to 1400 x 1050 SXGA+ compressed	Power Supply	100-240v, 50-60 Hz
Brightness	2300 ANSI Lumens	Power Consumption	265W Maximum, Standby <15w
Contrast Ratio	2000:1	Dimensions (W x H x D)	265 x 104 x 236mm (W x H x D)
Noise Level	27dB (ECO Mode)	INPUTS:	
Lamp Life	5000 hours (ECO mode)	Digital Video	DVI HDCP (HDMI via optional adaptor)
Lamp Type	200 watt SHP	PC RGB (RGB SCART)	15 Pin D-Sub VGA SCART RGB (supplied adaptor)
Video Compatibility	PAL, SECAM 625/576i/p NTSC 525/480i/p HD 720p/1080i	Analogue Component	15 Pin D-Sub VGA (component adaptor supplied)
Aspect Ratio	4:3/16:9 compatible	S-Video	4 Pin Mini Din
Projection Types	Front, Ceiling mounted, Rear, Rear ceiling mounted	Composite	RCA Jack
Throw Ratio	2.0 ~ 2.4:1 (Projection Distance:Image Width)	Stereo Audio	Mini Jack
Projection Distance	1.2m -10.0m (3.94' - 32.8')	Serial Control	RS232 Mini-DIN
Image Size	0.63 - 5.21m (27.6" to 267.2") Diagonal 4:3	OSD Languages	10 Languages including: English, German, Italian, French, Spanish, Norwegian and Russian
Keystone correction	± 16 degrees Vertical		
Remote Control	Infra-Red with PC page up/down function via USB		
Projection Lens	f=25.8 ~ 30.0mm, F/2.8 ~ 3.1, Manual Focus		
Weight	2.4 Kg		
Uniformity	85%		

